

Alloy Cone Midrange Driver.
 Butyl Rubber Surround.
 Alloy Bullet Phasing Plug.
 20 oz. Magnet Structure Weight.
 14K Gold Plated Spade Connectors.
 1" Silk Soft Dome Tweeter.
 Ferro-Fluid Voice Coil Cooling.
 Impedance Matching Network.
 Tweeter Flush & Surface Mounts.



ULTRADRIVE

aluminum
 component
 speakers



.....CWM5KIT

75 Watts RMS / 150 Watts
 Frequency Response: 65Hz - 22KHz
 Sensitivity: 92dB @ 1W/1M SPL
 4 Ohm System Impedance

*Complete with Wire Mesh Grills &
 Installation Hardware.*

.....CWM6KIT

100 Watts RMS / 200 Watts
 Frequency Response: 65Hz - 22KHz
 Sensitivity: 93dB @ 1W/1M SPL
 4 Ohm System Impedance

*Complete with Wire Mesh Grills &
 Installation Hardware.*

A tinted acrylic case houses this high fidelity dividing network. Features include audiophile-grade polypropylene capacitors and an optical bleed protection circuit for the tweeters. The Zobel network insures constant impedance & phase matching between the amplifier and speakers.

| MODEL | SIZE | DESCRIPTION | POWER RMS/PEAK | FREQUENCY RESPONSE | SPL 1W/1M | MOUNTING DEPTH | IMPEDANCE |
|-------|-------|--------------------------------|-------------------|-----------------------|--------------|-------------------|-----------|
| CT30 | 1/2" | Swivel Mylar Dome, Neodymium | 30/ 60 | 3.2KHz - 22KHz | 92dB | 3/4" | 4 ohms |
| CT40 | 1" | Silk Soft Dome, Neodymium | 60/120 | 1KHz - 20KHz | 93dB | 5/8" | 4 ohms |
| CT70 | 1" | Soft Dome Piezo, w/Transformer | 80/150 | 5KHz - 20KHz | 97dB | Surface | 4 ohms |
| CWM4 | 4" | Aluminum Alloy Cone Midrange | 60/120 | 85Hz - 5KHz | 92dB | 2" | 4 ohms |
| CWM5 | 5.25" | Aluminum Alloy Cone Midrange | 75/150 | 65Hz - 5KHz | 92dB | 2.5" | 4 ohms |
| CWM6 | 6.5" | Aluminum Alloy Cone Midrange | 100/200 | 65Hz - 5KHz | 93dB | 3" | 4 ohms |