

N.A.R

Audio



N.A.R.

Audio

TWO WAY SYSTEM



*a: with out grilles

Smart Kit

NEW!

Kevlar pp cone



SUBWOOFERS



10
N.A.R.-7



12
N.A.R.-7



SPECIFICATIONS



	IMPEDANCE	R M S	SENSITIVITY	FREQUENCY		
400	40hms	50 w	92db	90 hz	4"	51 mm
460	40hms	50 w	92db	70 hz	4x6"	51 mm
525	40hms	50 w	92db	60 hz	5"	54 mm
570	40hms	60 w	92db	42 hz	5x7"	54 mm
650	40hms	50 w	92db	58 hz	6"	54 mm
10-1	40hms	125 w	87db	20 hz	10"	110 ^{mm}
12-1	40hms	125 w	82db	20 hz	12"	130 ^{mm}

*Sensitivity: 1watt/1 meter - Frequency: a 20 khz/ +/- 4dB e Subs: a 200 khz/ +/- 4dB

Series CX, RX and TR

TRaudio
TRIAXIAL



TR 40

TR 50

TR 65

TR 57



RXaudio
COAXIAL



RX 40

RX 50

RX 65

RX 57



CXaudio
COAXIAL



400 CX

525 CX

650 CX

460 CX

570 CX



*Series CX, RX, TR e Smart Kit: sold in pairs

SPEAKER PARTS



NEO 50W
Neodymium magnet,
ferrofluid, V.C. 13mm e mylar dome



CHRISTAL 50W
Ferroelectric transducer,
PP dome



HT 5012
Neodymium magnet,
ferrofluid, V.C. 13mm
mylar dome

HTDT 132
Neodymium magnet,
ferrofluid,
V.C. 20mm, silk dome



TRIAxIAL
Neodymium magnet,
ferrofluid, mylar dome
and super tweeter Piezo

AUTOMOTIVE LOUDSPEAKERS SERIES

PARTS and COMPONENTS



TWEETERS



HT 5012



HTDT 132



GRILLES

HT-5000 5"

HT-7000 6"

MID BASS

525 CW / 650 CW



CROSSOVERS



HT-10 HC

2 way, 6dB, electrolytic capacitor and tweeter protection

HTCR-8-B

2 way, 12dB competition, mylar capacitor and tweeter protection



N.A.R.
Audio

NARL Importação e Exportação Ltda.

Alameda Araguaia, 560 /cj.1 - Alphaville

CEP 06455 000 - Barueri SP

Comercial: (11) 4191 - 6668 / 1888

info@nar-audio.com.br